

Model:
20" MirrorMedia MT20T



Specifications

PICTURE

| | |
|-----------------|---------------------|
| Screen Size | 20" |
| Screen Type | LCD / Mirror |
| Pixels | 800 x 600 |
| Colours | 16.7 Million |
| Panel Luminance | (Typical) 500 cd/m2 |
| Contrast | 600:1 |

AUDIO

Supported Sound System: B/G, L, I, D/K, Satellite, M/N, FM-Radio and NICAM
SAP and stereo detection for BTSC standard.
AVC, Automatic Volume Correction.
10W+10W amplified audio output.
Automatic Sound Selection (Mono/Stereo/bilingual)
Volume/Bass/Treble/Balance/Mute Adjustment.
SRS, optional.

TV CONNECTION

Composite Video 1 (CVBS) and audio L/R channels
Composite Video 2 (CVBS) and audio L/R channels or AV SCART
Dual S-Video connector and audio share with AV2.
Full SCART
Component YCbCr/YPbPr and audio left and right channel
Tuner, Cable or Antenna
PC D-Sub
DVI-I

TV VIDEO FEATURES

Advanced 3D motion adaptive de-interlace
Picture in Picture (Video on Graphics)
Picture on Picture
2:2/3:2 film mode detection
Brightness/contrast/hue/saturation adjustment
Support 4:3 < > 16:9 with linear and non-linear scaling
Support 50Hz < > 60Hz frame rate conversion
Support 50i to 100i and 60i to 120i double scan function
5 Screen Modes, 16:9, M1, M2, M3, M4, 4:3
VBI support Teletext 10 pages or 256 pages.
User Features 1. Sleep Timer, 2. Clock, 3. Area Channel Setting,
4. Channel Hidden / Delete.
OSD – 8 Languages
Remote Control – 32 Key IR

GENERAL

| | |
|-----------------------|--|
| Voltage | AC 100~240V/50~60Hz |
| Power Consumption | 180W |
| Stand-by | <2W |
| Weight | 9.75 Kg |
| Dimensions (WxHxD) mm | 452 x 365 x 66 (Excluding Picture Frame) |
| Stand | Optional |
| Wall Bracket | Inbuilt |
| Speakers | Optional |
| Picture Frame | Choice |