



# AQUAVISION


## Technical Information

### Model AVF 40-3 LCD

Available in MirrorVision® only



#### Bezel size



<u>Model</u>	<u>Screen Size</u>	<u>A</u> Overall Height	<u>B</u> Overall Width	<u>C</u> Cut out Height	<u>D</u> Cut out Width	<u>E</u> Max Depth
<b>AVF-40-LCD</b>	<b>1016mm</b>	<b>692mm</b>	<b>1049mm</b>	<b>683mm</b>	<b>1040mm</b>	<b>135mm</b>

#### Screen

LCD TFT  
WXGA 1366 x 768  
PAL/SECAM-B/G, D/K, L  
Full Auto Tuning  
TeleText/FastText  
Heated Screen

#### Inputs

1 x HDMI (High Definition Multimedia Interface)  
1 x Component in(Y/Pb/Pr) 480p/576p/720p/1080i  
2 x Scart (1x Fully Wired, 1 x Half Wired)  
1 x Composite AV (Yellow, Red, and White)  
1 x S- Video  
1 x PC D- Connector + 3.5mm Audio  
1 x Analogue Tuner  
1 x Digital Tuner (Freeview with Cam card slot)

#### Sound

Nicam Stereo  
2 x 10 Watts (RMS)  
Graphic Equaliser

#### Power

Auto sensing 90-240VAC  
IEC "Cold" input connector.  
Power Consumption 130W  
Standby Consumption <3w

#### Optional

Hard wired control panel with switch mimic connection.

#### Speaker details

