



CE42LH2WP

- Fully Approved IP66 Weatherproof screen, Protected against powerful water jets and dust ingress
- Screen Dimension 42" (105cm)
- Full HD (1920 x 1080)
- Robust Screen Surface with Anti Reflective Tempered Glass
- Winter Mode -20 – 45c Operation
- Anti Corrosive Anodised Aluminium Cabinet
- Suitable for 24/7 Applications
- Picture in Picture Mode
- Network Content Delivery, Control and Monitoring (Optional)
- Built in Video Wall Capability

CE42LH2WP

TECHNICAL DETAILS

CE42LH2WP

Category	Professional LCD Monitor
Type	LCD
IP Rating	IP66
Screen size (diagonal image)	42" (105cm)
Active screen area (W x H)	93 x 52.3cm
Aspect Ratio	16:9
Resolution in pixels	1920 x 1080
Pixel Pitch	0.681 x 0.4845mm
Brightness	500cd/m
Contrast Ratio	1200:1
Viewing angle	178 (Vertical and Horizontal)
Response Time	9 ms
Grey scale value	8 bit
Number of colours	16.7m
Colour Systems	PAL, NTSC, SECAM
Computer Compatibility	VGA, SVGA, XGA, SXGA, WXGA, UXGA
Input Terminals	1 x Scart (RGB, Video/Audio) 5 x BNC (RGBHV, Y,Pb,Pr) 1 x BNC (Video) 1 x Dsub15 (RGB) 1 x DVI-D (HDCP)
Audio in	2 x RCA 1 x Mini Jack
Control	1 x Dsub9 (RS232)
Output Terminals	5 x BNC (RGBHV, Y,Pb,Pr) 1 x BNC (Video)
Audio out	2 x RCA External Speaker out (2 x 6w)
Control	1 x Dsub9 (RS232)
Operating Temperature	-20 – 45 c
Maximum resilience	100N/mm2
Voltage	AC 100 – 240v 50/60Hz
Power Consumption	200w / 1w Standby
Dimensions (W x H x D)	1027 x 620 x 167.5mm
Weight	40kg
VESA Mounting sizes	200 x 200mm
Colour of cabinet	Silver, Anodized Aluminum
Warranty	2 Year
Standard Accessories	Owner Manual, Remote Control, Power Cable
Optional Accessories	POA-PN02 (Network Control Box with Content Delivery)
Special Features	Anodized aluminium bezel, Weatherproof, Anti-reflective tempered glass, 24/7 approved, portrait mode.


* You can use the distance calculator at www.uk.sanyo.com to determine exact image sizes and distances

Technical specifications subject to change without notice. Status 02/2010

Telephone: 0116 238 8397

Email: W@terproof.tv

Visit: www.waterprooftv.co.uk





UNIAMP

This versatile stereo amplifier has four selectable inputs (DVD, CD, tape, and DVD karaoke) and two microphone inputs with individual volume controls and echo control. The master output has a two-band EQ allowing adjustment of the bass and treble frequencies, there is also a master balance and volume control.

- A high output power of 2 x 32W max
- Incorporates a toroidal transformer
- Blue power on LED
- Features 2-band tone controls and a MASTER volume control
- Microphone inputs are fitted with separate volume controls and echo effect
- 4 stereo LINE inputs via RCA phono sockets
- Spring clip terminal speaker connections
- 2 microphone inputs via 6.3mm gold plated jack sockets
- With fixed mains lead

- **Power supply** 230Vac, 50Hz
- **Input sensitivity : Line** 500mV
- **Output power @ 8 Ohms** 2 x 12.5W rms / 2 x 25W max
- **Output power @ 4 Ohms** 2 x 16W rms / 2 x 32W max.
- **Dimensions** 95 x 250 x 240mm
- **Minimum impedance** 4 Ohms
- **Input sensitivity : Mic (unbalanced)** 2mV
- **Weight** 1.42kg

Technical specifications subject to change without notice.



WPSPKR

10.2cm (4") INDOOR/OUTDOOR SPEAKER

These stylish two-way, weather resistant speakers are suitable for indoor and outdoor applications. These speakers will excel as a straightforward stereo pair, for multimedia or as part of a surround sound system. Although small the speakers have a big sound giving 100W RMS. Supplied with wall-mount brackets.

- Weather resistant, IP35 rated
- 2-way
- Polypropylene housing with aluminium grille
- Polypropylene woofer and fluid-cooled Polycarbonate tweeter
- Gold-plated compression terminal posts

■ **Woofer** 102mm (4")

■ **Power rms** 100W

■ **Impedance** 8 Ohms

■ **Dimensions** 135 x 205 x 136mm

Tweeter 20mm (3/4")

Frequency response 80Hz - 20kHz

Sensitivity 88dB @ 1W/1m

Weight 1.4kg

Technical specifications subject to change without notice.