



CE52LH2WP



**FULL
HD
1080p**

- Fully-approved IP66 weatherresistant, protected against powerful water jets and against short-term flooding
- Screen size 132 cm (52 inch)
- Full HD resolution (1,920 x 1,080) in 16 : 9 aspect ratio
- Winter mode: guaranteed monitor usability at temperatures ranging from -20 °C to +45 °C
- Network integration (optional) for maintaining and controlling the monitor on the LAN
- Picture-in-Picture and Picture-by-Picture function
- Vandalism- and tamper-proof anti-reflective glass, anti-corrosive cabinet
- Ideally suited for various indoor and outdoor installations
- 3 years warranty

CE52LH2WP

| TECHNICAL DATA | CE52LH2WP |
|------------------------------|--|
| Category | Professional LCD monitor |
| Type | Liquid Crystal Display Panel * |
| IP Rating | IP66 foreign bodies and water protection |
| Screen size (diagonal image) | 52" (132 cm) |
| Active Screen Area (W x H) | 115.2 x 64.8 cm |
| Aspect Ratio | 16:9 |
| Resolution in pixels | 1,920 x 1,080 (HDTV 1,080p) |
| Pixel pitch | 0.6 x 0.6 mm |
| Brightness | 700 cd/m ² |
| Contrast Ratio | 2000 : 1 |
| Viewing Angle | 176° (horizontal and vertical) |
| Response time | 8 ms (gray to gray) |
| Grey scale value | 8 bit |
| Number of colors | 16.7 Mio |
| Color systems | PAL, NTSC3.58 (AV in), SECAM |
| Computer compatibility | U-XGA, W-XGA, S-XGA, XGA, S-VGA, VGA, 1,080i |
| Input Terminals | D-Sub15 5 x BNC (RGBHV, Y-Pb/Cb-Pr/Cr) Component (Y, Pb, Pr) BNC (Video) Video D-Sub9 (RS232) 2 x RCA (R/L mono) for audio DVI-D (digital/HDCP) 3.5 mm stereo jack for audio |
| Output Terminals | 5 x BNC (RGBHV, Y-Pb/Cb-Pr/Cr) Component (Y, Pb, Pr) BNC (Video) D-Sub9 (RS232) 2 x RCA (R/L mono) for audio External speaker output (2 x 8 W) |
| Operating Temperature | -20 °C - 40 °C |
| Storage Temperature | -20 °C - 60 °C |
| Depth of front glass | 6 mm |
| Mechanical strength | 100 N/mm ² |
| Voltage | 100 - 240 V (50 - 60 Hz) |
| Power Consumption | 360 W/0.8 W (stand-by mode) |
| Dimensions (W x H x D) | 1304 x 804 x 227 mm |
| Weight | 83 kg |
| Vesa Mounting Sizes | 420 x 516 mm , 997 x 420 mm |
| Color of cabinet | Silver |
| Warranty | 3 years, 24-hr replacement service (D/CH/I/F - except overseas) |
| Standard accessories | user manual, remote control, batteries, power cable |
| Optional Accessories | LD Net Organizer Plus (POA-LN02) , Wall mount (POA-WM52H), Wall mount (POA-WM52V) |
| Special feature | weatherproof, dustproof, anodized aluminium case, vandalism-resistant, anti-reflective glass screen, winter mode, portrait and landscape mode, picture-in-picture and picture-by-picture function, extensive input & output terminals, video wall function |

* IP = Protection class



Technical specifications subject to change without notice. Date 04/2010

